Risk Assessment	Manufacturer: Lingong Heavy Machinery Co., Ltd. machine: Mobile Elevated Work Platform	author: Lingong date: 2023.1.1	
according to AS 4024.1301	serial number:T20J		LGMG

1	Determination of limits, intended use	See below		Reference to additional documents		
1.1	use allowed	The mobile elevated work platform	allows users to work at a certain height	Manual		
1.2	restrictions, limits of use allowed	The machine cannot be used to ot	her propose	Manual		
1.3	foreseeable misuse/misapplication	See AS/NZS 1418.10:2011 clause 1:	NZS 1418.10:2011 clause 1: scope.			
2	Field of use	See below	w			
	private	N/A				
	commercial	Professional	onal			
3	User population	Task	Qualification			
	qualified personnel	Required	YES	Training Evidence		
	laities	N/A	N/A	N/A		
	apprentices	N/A	N/A	N/A		
	private use only:					
	children (declare age class)	age above years		N/A		
	older people			N/A		
	handicapped	kind of handicap		N/A		
4	Materials	See below				
4.1	dangerous operating supplies	🛛 Electricity 🖂 Hydraulic 🗌 Pneu	umatic 🗌 Thermal 🔲 Radiation	Manual		
4.2	Dangerous materials in the parts the machine is consisting of	The machine is not consisting of da	machine is not consisting of dangerous materials			
4.3	Dangerous materials which may be processed by the machine	No dangerous materials processed	by the machine	N/A		

The phases of life according to AS 4024 include: transport, assembling, installation, placing into operation, setup, teaching, programming, changeover, working process, cleaning, process interference troubleshooting, fault clearance, maintenance, placing out of operation, disassembling, waste disposal

Copyright: TÜV SÜD Product Service GmbH Gottlieb-Daimler-Straße 7 70794 Filderstadt phone: +49 (0)711 7005-295; Fax: -587



a						author: Lingong date: 2023.1.1		
	Identification of hazards			Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

1.1	ransport, assembl Hazards	Errors of fitting	Crushing	Machine, components and accessories	Inhorontly coto machinery design	AS/NZS		OK	
1.1	associated with	g			Inherently safe machinery design	1418.10:2011 and			
	all tasks	⊠Lifting	Cutting or		and inform users of the residual risks:	MSD as reference,			
			severing		TISKS:				
		⊠Loading	— ———————————————————————————————————		Detail description for transportation				
		Dealing	Friction or abrasion		Detail description for transportation, assembling and installation of machine				
		Packing	abrasion		are mentioned in manual.				
		⊠Transportation	⊠Impact						
		⊠Unloading							
		N							
		Unpacking	Shearing						
		⊠Packing	Stabbing or						
			puncture						
		⊠Adjustments	-						
		Assembly							
		⊠Connecting to							
		disposal system							
		(e.g. exhaust							
		system, waste							
		water installation)							
		Connection to							
		power supply							
		Demonstration							
		Feeding, filling, loading of ancillary							
		fluids (e.g.							

risk assessment-T20J.docx date: 1/1/2024 page 2 of 23

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1			
	Identification of hazards						ion, AS 4024 or ISO 1 or type I/II/III	
Phase of life			Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement
		lubricant, grease, glue)						

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1					
	Identific	cation of hazards						tion, AS 4024 or ISO 1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	P pl	Statement
1.2	Hazards associated with all tasks	 ➢ Fixing, anchoring ➢ Preparations for the installation (e.g. foundations, vibration isolators) ➢ Running the machine without load ➢ Testing ➢ Trials with load or maximum load □ Fencing 	See above	See above	See above	AS/NZS 1418.10:2011 and MSD as reference,				οκ
2 Pla	acing into operati	on		1		1				1
2.1	Hazards associated with all tasks	Refer to 1+3	Refer to 1+3	Refer to 1+3	Refer to 1+3	Refer to 1+3				ОК
3 Se	tup, teaching, pro	ogramming, change	eover	1	1	1				1
3.1	Hazards associated with all tasks	Adjustment and setting of protective devices and other components	Crushing	Machine and components	Inherently safe machinery design and inform users of the residual risks:	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) + MSD as reference,				ок
Gottlieb-Da 70794 Fild	TÜV SÜD Product Ser aimler-Straße 7 erstadt 9 (0)711 7005-295; Fax								r	isk assessment-T20J.docx date: 1/1/2024 page 4 of 23

Risk A according	ssessmen to AS 4024	-			author: Lingong date: 2023.1.1				
Identific	cation of hazards						ation, AS 4024 or ISO 9-1 or type I/II/III		
Phase Hazard group, of life type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	SF	P	pl	Statement
	 Adjustment and setting or verification of functional parameters of the machine Clamping /fastening the workpiece Feeding, filling, loading of raw material ⊠ Functional test, trials Mounting or changing tools, tool setting □ programming verification of the final product 	 □Friction or abrasion □Inpact □Injection ☑ Shearing ☑ Stabbing or puncture 		Refer to AS/NZS 1418.10:2011, clause 7 and manual					

a	Risk Assessment according to AS 4024.1301 Identification of hazards			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1			
	Identification of hazards				Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

1	Mechanical	Acceleration,	Being run	Inherently safe machinery design		ok
	Hazards	deceleration (kinetic energy)	over □Being thrown	and construction, take necessary protection measures and inform users of the residual risks:	1418.10:2011 + AS 60204.1-2005(+A1)	
		Approach of a moving element to	⊠Crushing	Refer to AS/NZS 1418.10:2011, clause 7 and manual	7	
		a fixed part	⊠Cutting or severing			
		Elastic elements	⊠Drawing-in or trapping			
		⊠Falling objects	⊠ Entanglement			
		Gravity (stored energy)	⊠Friction or abrasion			
		Height from the ground	⊠Impact			
		⊠High pressure				
		⊠Machinery mobility	⊠Shearing ⊠Slipping,			
		⊠Rotating fi elements	tripping and falling			
			Stabbing or puncture			
		surface				

risk assessment-T20J.docx date: 1/1/2024 page 6 of 23

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery Co., Ltd. machine: Mobile Elevated Work Platform serial number: T20J		author: Lingong date: 2023.1.1		
	Identification of hazards					ation, AS 4024 or ISC 9-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement
		⊠Stability ⊡Vacuum						

a	Risk Assessment according to AS 4024.1301					author: Lingong date: 2023.1.1					
	Identific	ation of hazards			Risk evaluation		Risk		stimation, AS 4024 or 13849-1 or type I/II/III		
Phase of life			Potential consequences	occurrence or protection goal	Description of solution	Standards	S F	Р	pl	Statement	
4.2	See 4.1/4.3	See 4.1/4.3	See 4.1/4.3	See 4.1/4/3	See 4.1/4.3	See 4.1/4/3				See 4.1/4.3	
4.3	Electrical Hazards	 ☐ Arc ☐ Electromagnetic phenomena ☑ Electrostatic phenomena ☑ Live parts ☐ Not enough distance to live parts under high voltage ☑ Overload ☑ Parts which have become live under fault conditions ☑ Short-circuit ☐ Thermal radiation 	☑ Burn ☑ Chemical effects ☑ Effects on medical implants ☑ Electrocution ☑ Falling, being thrown ☑ Fire □ Projection of molten particles ☑ Shock	Any risk related to electrical fault will be checked automatically and view check according to manual	Inherently safe machinery design and construction: Refer to AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) No electronic circuit for safety circuit	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) as reference,				See 4.1	
4.4	Thermal Hazards	Explosion Flame Objects or materials with a high or low temperature	Bun Dehydration Discomfort Frostbite	Not relevant	Not relevant	N/A				N/A	

risk assessment-T20J.docx date: 1/1/2024 page 8 of 23

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery Co., Ltd. machine: Mobile Elevated Work Platform serial number: T20J		author: Lingong date: 2023.1.1				
	Identification of hazards								on, AS 4024 or ISO or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F	Ρ	pl	Statement
		☐Radiation from heat sources	☐Injuries by the radiation of heat sources ☐Scald							

а		Assessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: T20J		author: Lingong date: 2023.1.1				
	Identifie	cation of hazards			Risk evaluation		Risl			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	FP	pl	Statement
4.5	Noise hazards	 □Cavitation phenomena □Exhausting system □Gas leaking at high speed ○Manufacturing process (stamping, cutting etc) ○Moving parts □Scraping surfaces □Unbalanced rotating parts □Whisting pneumatics ○Worn parts 	 ☑ Discomfort ☑ Loss of awareness ☑ Loss of balance ☑ Permanent hearing loss ☑ Stress ☑ Tinnitus ☑ Tiredness ☑ Any other (e.g. mechanical, electrical) as a consequence of an interference with speech communicatio n or with acoustic signals 	Refer to comments.	Inform users of the residual risks: The manual has indicated the sound pressure level below 70dB	AS/NZS 1418.10:2011+MSD				ОК
4.6	Vibration Hazards	 □Cavitation phenomena ☑Misalignment of moving parts 	⊠Discomfort □Low-back morbidity	Vibration will neither make the passenger uncomfortable nor damage the structure	Inherently safe machinery design protects the vibration from discomforting passengers and from damaging the structure. Dynamic load test performed and found	AS/NZS 1418.10:2011				ОК

risk assessment-T20J.docx date: 1/1/2024 page 10 of 23

a		Assessmer to AS 4024		Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1						
	Identifi	cation of hazards							ation, AS 4024 or ISO 9-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	ption of solution Standards			SFP		Statement
		 Mobile equipment Scraping surfaces Unbalanced rotating parts Vibrating equipment Worn parts 	 □Neurological discorder □Osteo- articular discorder □Trauma of the spine □Vascular disorder 		satisfactory						

a		Assessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1				
	Identifi	cation of hazards			Risk evaluation		Risk estima 13849		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P	pl	Statement
4.7	Radiation Hazards	 ☐Lionising radiation source ☐Low frequency electromagnetic radiation ☐Optical radiation linfrared, visible and ultraviolet), including laser ☐Radio frequency electromagnetic radiation 	 ☐ Burn ☐ Damage to eyes and skin ☐ Effects on reproductive capability ☐ Genetic mutation ☐ Headache, insomnia, etc. 	Not relevant	Not relevant	N/A			N/A
4.8	Material/ substance hazards	 Aerosol Biological and microbiological (viral or bacterial) agent Combustible Dust Explosive Fibre Flammable ⊠Fluid 	□Breathing difficulties, suffocation □Cancer □Corrosion □Effects on reproductive capability ☑Fire □Infection □Mutation □Poisoning	Not relevant	Not relevant	N/A			N/A

risk assessment-T20J.docx date: 1/1/2024 page 12 of 23

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1					
	Identification of hazards							sk estimation, AS 4024 13849-1 or type I/II/I		
Phase of life				occurrence or protection goal	Description of solution	Standards	S	FP	pl	Statement

a		Assessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platform serial number: T20J		author: Lingong date: 2023.1.1					
	Identifie	cation of hazards			Risk evaluation						n, AS 4024 or ISO or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Рp	bl	Statement
4.9	Ergonomic hazards	 Access Disign or location of indicators and visual displays units Design, location or identification of control devices Effort Flicker, dazzling, shadow, stroboscopic effect Local lighting Mental overload/underloa d Posture Repetitive activity Visibility 	 ☑ Discomfort ☑ Fatigue ☑ Musculoskelet al disorder ☑ Stress ☑ Any other (e.g.mechanica I, electrical) as a consequence of human error 	The position of control device need to be taken into account The access means need to be taken into account	Inherently safe machinery design	AS/NZS 1418.10:2011 as reference,					ЭК
4.10	Hazards associated with environment in	Dust and fog Electromagnetic	☐Burn ☐Slight	Working condition and EMC need to be considered	Inherently safe machinery design and construction and inform users of the residual risks:	AS/NZS 1418.10:2011 + MSD as reference,				C	DK

risk assessment-T20J.docx date: 1/1/2024 page 14 of 23

а		ssessmen to AS 4024		Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: T20J		author: Lingong date: 2023.1.1						
	······································				Risk evaluation					ation, AS 4024 or ISO 9-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s I	FF	p pl	Statement		
	which the machine is used	disturbance Lighting Moisture Pollution Snow Temperature Water Wind Lack of oxygen	disease Slipping, falling Suffocation Any other as a consequence of the effect caused by the sources of the hazards on the machine or parts of the machine		 1.2204/108/EEC addressed 2. Lighting for the control panel is provided and the lighting for access is indicated in the manual 3. Snow, wind loads are considered in the design and structural calculation 4. Ambient temperature is defined in the manual 5. All electric parts are protected by the enclosure with enough IP degree according to AS/NZS 1418.10:2011 							

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platform serial number: T20J		author: Lingong date: 2023.1.1	_				
	Identific	cation of hazards			Risk evaluation						on, AS 4024 or ISO or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement
4.11	Combination of hazards	E.g.repetitive activity + effort + high environmental temperature	E.g. dehydration, loss of awareness, heat stroke	Not relevant	Not relevant	N/A					N/A
4.12	Energy loss ,breaking down hazards	 ☑ Failure of energy supply (incl. control circuits) ☑ Unexpected ejection of machine parts or fluid □ Errors of fitting 	□ Being thrown ⊠Cutting or severing □ Drawing-in or trapping □ Entanglement ⊠Friction or abrasion □Inpact □Shearing ⊠Slipping, tripping and falling □Suffocation	All risk related to unexpected starting or energy loss need to be taken into account	Inherently safe machinery design and construction, take necessary protection measures: 1. Brakes and cut-off valves are designed to be engaged as soon as the power losses, preventing the lift from falling.	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) + MSD as reference,					ок

a				to AS 4024.1301 machine: Mobile Elevated Work Platform c							
										on, AS 4024 or ISO or type I/II/III	
Phase of life				occurrence or protection goal	Description of solution	Standards	s	F	Ρŗ	pl	Statement

a	Risk Assessment according to AS 4024.1301 Identification of hazards		-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1			
	Identific	ation of hazards			Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

С	Hazards associated with	Adjustments	Crushing	Machine , components and accessories	Inherently safe machinery design and inform users of the residual	AS/NZS 1418.10:2011 + MSD as reference,	0	K
	all tasks	disinfection	severing		risks:			
		Dismantling /removal of parts, components,	⊠Friction or abrasion		Refer to AS/NZS 1418.10:2011 and manual			
		devices of the machine	⊠Impact					
		⊠lsolation end	Shearing					
		energy dissipation	Stabbing or puncture					
		⊠Replacement of worn parts						
		Resetting						
		□Restoring fluid levels						
		☐Verification of parts, components, devices of the						
		machine						

risk assessment-T20J.docx date: 1/1/2024 page 18 of 23

ac	-	ssessmen to AS 4024	It	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J		author: Lingong date: 2023.1.1			
	Identific	ation of hazards		Risk evaluation					on, AS 4024 or ISO or type I/II/III
Phase of life			Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P	pl	Statement

a		Risk Assessment ording to AS 4024.1301 Identification of hazards		Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1			
	Identific	ation of hazards			Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

6 Pi	rocess interference	es, troubleshooting	g, fault clearand				
6 Pr 6.1	rocess interference Hazards associated with all tasks	es, troubleshooting Adjustments	g, fault clearance ⊠Crushing ©Cutting or severing □Friction or abrasion ⊠Impact □Injection Shearing Stabbing or puncture	e Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks: Refer to AS/NZS 1418.10:2011 clause 5 and manual	AS/NZS 1418.10:2011+ AS 60204.1-2005(+A1) + MSD as reference	ОК
		from jam ⊠Repairing ⊠Replacement of parts, components, devices of the machine ⊠Rescue of trapped persons ⊠Resetting					

Risk Assessment according to AS 4024.1301			-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J								
	Identification of hazards								tion, AS 4024 or ISO -1 or type I/II/III			
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards S			Р	pl	Statement	
		⊠Verification of parts, components, devices of the machine										

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1			
	Identific	ation of hazards					ion, AS 4024 or ISO 1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

7.1	Hazards associated with	Adjustments	□Crushing ☑Cutting or	Machine , components and accessories	Inherently safe machinery design and inform users of the residual	AS/NZS 1418.10:2011 as reference	ОК
	all tasks		severing		risks:		
		Dismantling /removal of parts, components,	Friction or abrasion		Refer to AS/NZS 1418.10:2011 clause 7		
		devices of the machine					
		Housekeeping	☐Injection ⊠Shearing				
		⊠Isolation end energy dissipation	Stabbing or puncture				
		Lubrication					
		⊠Replacement of worn parts					
		⊠Resetting					
		☐Restoring fluid levels					
		⊠Verification of parts, components, devices of the machine					

8 Placing out of operation, disassembling, waste disposal

Copyright: TÜV SÜD Product Service GmbH Gottlieb-Daimler-Straße 7 70794 Filderstadt phone: +49 (0)711 7005-295; Fax: -587

risk assessment-T20J.docx date: 1/1/2024 page 22 of 23

Risk Assessment			-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T20J	author: Lingong date: 2023.1.1						
Identification of hazards										tion, AS 4024 or ISO -1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Р	pl	Statement
8.1	Hazards associated with all tasks	 ☑ Disconnection and energy dissipation ☑ Dismantling ☑ Lifting ☑ Loading ☑ Packing ☑ Transportation ☑ Unloading 	 □Crushing □Crushing or severing □Friction or abrasion □Impact □Injection □Shearing □Stabbing or puncture 	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks: Refer to AS/NZS 1418.10:2011	AS/NZS 1418.10:2011 as reference					ОК