Risk Assessment	Manufacturer: Lingong Heavy Machinery Co., Ltd. machine: Mobile Elevated Work Platform	author: Lingong date: 2023.06.01	
according to AS 4024.1301	serial number: M0810JE		LGMG

1	Determination of limits, intended use	See below		Reference to additional documents				
1.1	use allowed	The mobile elevated work platform	allows users to work at a certain height	Manual				
1.2	restrictions, limits of use allowed	The machine cannot be used to ot	her propose	Manual				
1.3	foreseeable misuse/misapplication	See AS/NZS 1418.10:2011 clause 1	/NZS 1418.10:2011 clause 1: scope.					
2	Field of use	See below						
	private	N/A		N/A				
	commercial	Professional		Manual				
3	User population	Task	Qualification					
	qualified personnel	Required	YES	Training Evidence				
	laities	N/A	N/A	N/A				
	apprentices	N/A	N/A	N/A				
	private use only:							
	children (declare age class )	age above years		N/A				
	older people			N/A				
	handicapped	kind of handicap		N/A				
4	Materials	See below						
4.1	dangerous operating supplies	🛛 Electricity 🖾 Hydraulic 🗌 Pne	umatic 🗌 Thermal 🗌 Radiation	Manual				
4.2	Dangerous materials in the parts the machine is consisting of	The machine is not consisting of d	angerous materials	Manual				
4.3	Dangerous materials which may be processed by the machine	No dangerous materials processed	I by the machine	NA				
Copyright	shooting, fault clearance, maintenance, placing out of operation :: TÜV SÜD Product Service GmbH Daimler-Straße 7	, installation, placing into operation, , disassembling, waste disposal	setup, teaching, programming, changeover, working process, cleaning, process in	sk assessment-M0810JE date: 01/06/2024				
Copyright Gottlieb-D 70794 File	:: TÜV SÜD Product Service GmbH Daimler-Straße 7	, asassanising, waste uisposal	1300					

This form was developed by TÜV SÜD Product Service GmbH. The user is responsible for the content.

ac		ssessmer to AS 4024	it	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01		
	Identification of hazards				Risk evaluation			on, AS 4024 or ISO or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement
1 Tra	nsport, assembli	ng, installation						

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE						_			
	Identific	ation of hazards		Risk evaluation							ation, AS 4024 or ISO 9-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution Standards			F	Р	pl	Statement		
1.1	Hazards associated with all tasks	<ul> <li>Errors of fitting</li> <li>Lifting</li> <li>Loading</li> <li>Packing</li> <li>Transportation</li> <li>Unloading</li> <li>Unpacking</li> <li>Packing</li> <li>Adjustments</li> <li>Adjustments</li> <li>Assembly</li> <li>Connecting to disposal system (e.g. exhaust system, waste water installation)</li> <li>Connection to power supply</li> <li>Demonstration</li> <li>Feeding, filling, loading of ancillary fluids (e.g.</li> </ul>	<ul> <li>☑ Crushing</li> <li>☑ Cutting or severing</li> <li>☑ Friction or abrasion</li> <li>☑ Impact</li> <li>☑ Injection</li> <li>☑ Shearing</li> <li>☑ Stabbing or puncture</li> </ul>	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks: Detail description for transportation, assembling and installation of machine are mentioned in manual.	AS/NZS 1418.10:2011 and MSD as reference,					OK		

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE	•	author: Lingong date: 2023.04.01		
	Identification of hazards						ion, AS 4024 or ISO 1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement
		lubricant, grease, glue)						

a	_	ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: M0810JE		author: Lingong date: 2023.04.01						
	Identific	cation of hazards			Risk evaluation		Ri			stimation, AS 4024 or 3849-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement	
1.2	Hazards associated with all tasks	<ul> <li>☐ Fixing, anchoring</li> <li>☐ Preparations for the installation (e.g. foundations, vibration isolators)</li> <li>☐ Running the machine without load</li> <li>☐ Testing</li> <li>☐ Trials with load or maximum load</li> <li>☐ Fencing</li> </ul>	See above	See above	See above	AS/NZS 1418.10:2011 and MSD as reference,					ОК	
2.1	acing into operati Hazards associated with all tasks	on Refer to 1+3 ogramming, change	Refer to 1+3	Refer to 1+3	Refer to 1+3	Refer to 1+3					ок	

a	Risk Assessment       Manufacturer: Lingong Heavy Machinery Co., Ltd.         machine: Mobile Elevated Work Platform         serial number: M0810JE				machine: Mobile Elevated Work Platform date: 2023.04.					
	Identifie	cation of hazards			Risk evaluation			tisk estimation, AS 4024 c 13849-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal Description of solution Stand			SF	Рp	ы	Statement
3.1	Hazards associated with all tasks	<ul> <li>Adjustment and setting of protective devices and other components</li> <li>Adjustment and setting or verification of functional parameters of the machine</li> <li>□Clamping /fastening the workpiece</li> <li>□Feeding, filling, loading of raw material</li> <li>⊠Functional test, trials</li> <li>⊠Mounting or changing tools, tool setting verification</li> <li>□Verification of the final product</li> </ul>	<ul> <li>☑ Crushing</li> <li>☑ Cutting or severing</li> <li>☐ Friction or abrasion</li> <li>☑ Impact</li> <li>☐ Injection</li> <li>☑ Shearing</li> <li>☑ Stabbing or puncture</li> </ul>	Machine and components	Inherently safe machinery design and inform users of the residual risks: Refer to AS/NZS 1418.10:2011, clause 7 and manual	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) + MSD as reference,			O	Κ

risk assessment-M0810JE date: 01/06/2024 page 6 of 27

a	_	ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01		
	Identific	ation of hazards			Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

a		ssessmen to AS 4024	t	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01				
	Identification of hazards				Risk evaluation		Risk			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	SF	Р	pl	Statement
4 Wo	orking process									

a		Assessmen to AS 4024	-		Manufacturer: Lingong Heavy Machinery Co., Ltd.author: Lingongmachine: Mobile Elevated Work Platformdate: 2023.04.01serial number: M0810JE								
	Identifie	cation of hazards			Risk evaluation					Risk estimation, AS 40 13849-1 or type I/			
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl			Statement			
4.1	Mechanical Hazards	<ul> <li>Acceleration, deceleration (kinetic energy)</li> <li>Angular parts</li> <li>Approach of a moving element to a fixed part</li> <li>Cutting parts</li> <li>Cutting parts</li> <li>Elastic elements</li> <li>Falling objects</li> <li>Gravity (stored energy)</li> <li>Height from the ground</li> <li>High pressure</li> <li>Machinery mobility</li> <li>Rotating elements</li> <li>Rough, slippery surface</li> <li>Sharp edges</li> </ul>	Being run         over         □ Being         thrown         ⊠ Crushing         ⊠ Crushing or         severing         ⊠ Drawing-in         or trapping         ⊠ Entanglement         ⊠ Friction or         abrasion         □ Injection         ⊠ Shearing         ⊠ Slipping,         tripping and         falling         □ Stabbing or         □ Suffocation		Inherently safe machinery design and construction, take necessary protection measures and inform users of the residual risks: Refer to AS/NZS 1418.10:2011, clause 7 and manual	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1)				ok			

risk assessment-M0810JE date: 01/06/2024 page 9 of 27

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE	Co., Ltd.	author: Lingong date: 2023.04.01		
	Identification of hazards						nation, AS 4024 or ISC 49-1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement
		⊠Stability ⊡Vacuum						

a		Assessmen to AS 4024	-			author: Lingong date: 2023.04.01					
	Identifie	cation of hazards			Risk evaluation					tion, AS 4024 or ISC 1 or type I/II/III	
Phase of life	fe         type         type         consequen           See 4.1/4.3         See 4.1/4.3         See 4.1/4.3			occurrence or protection goal	Description of solution	Standards	s	S F	Р	pl	Statement
4.2	See 4.1/4.3	See 4.1/4.3	See 4.1/4.3	See 4.1/4/3	See 4.1/4.3	See 4.1/4/3		$\top$			See 4.1/4.3
4.3	Electrical Hazards	<ul> <li>□ Arc</li> <li>□ Electromagnetic phenomena</li> <li>○ Electrostatic phenomena</li> <li>○ Live parts</li> <li>□ Not enough distance to live parts under high voltage</li> <li>○ Overload</li> <li>○ Parts which have become live under fault conditions</li> <li>○ Short-circuit</li> <li>□ Thermal radiation</li> </ul>	⊠Burn         □Chemical         effects         □Effects on         medical         implants         ⊠         Electrocution         ⊠Falling,         being thrown         ⊠Fire         □Projection         of molten         particles         ⊠Shock	Any risk related to electrical fault will be checked automatically and view check according to manual	Inherently safe machinery design and construction: Refer to AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) No electronic circuit for safety circuit	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) as reference,					See 4.1

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE	author: Lingong date: 2023.04.01						
	Identific	ation of hazards			Risk evaluation						ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement
4.4	Thermal Hazards	Explosion Flame Objects or materials with a high or low temperature Radiation from heat sources	□Bun □Dehydration □Discomfort □Frostbite □Injuries by the radiation of heat sources □Scald	Not relevant	Not relevant	N/A					N/A

aco	-	ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: M0810JE	author: Lingong date: 2023.04.01						
	Identific	ation of hazards			Risk evaluation		Ris				on, AS 4024 or ISO or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	urrence or protection goal Description of solution Standards		s	F	ΡI	pl	Statement
4.5 N	loise hazards	<ul> <li>□Cavitation phenomena</li> <li>□Exhausting system</li> <li>□Gas leaking at high speed</li> <li>☑Manufacturing process (stamping, cutting etc)</li> <li>☑Moving parts</li> <li>□Scraping surfaces</li> <li>□Unbalanced rotating parts</li> <li>□Whisting pneumatics</li> <li>☑Worn parts</li> </ul>	<ul> <li>☑ Discomfort</li> <li>☑ Loss of awareness</li> <li>☑ Loss of balance</li> <li>☑ Permanent hearing loss</li> <li>☑ Stress</li> <li>☑ Tinnitus</li> <li>☑ Tiredness</li> <li>☑ Any other (e.g. mechanical, electrical) as a consequence of an interference with speech communicatio n or with acoustic signals</li> </ul>	Refer to comments.	Inform users of the residual risks: The manual has indicated the sound pressure level below 70dB	AS/NZS 1418.10:2011+MSD					ЭК

а		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01	date: 2023.04.01					
	Identific	ation of hazards			Risk evaluation					tion, AS 4024 or IS 1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S	F	P pl	Statement		
4.6	Vibration Hazards	<ul> <li>□ Cavitation phenomena</li> <li>□ Misalignment of moving parts</li> <li>□ Mobile equipment</li> <li>□ Scraping surfaces</li> <li>□ Unbalanced rotating parts</li> <li>□ Vibrating equipment</li> <li>□ Worn parts</li> </ul>	<ul> <li>☑ Discomfort</li> <li>□ Low-back morbidity</li> <li>□ Neurological discorder</li> <li>□ Osteo- articular discorder</li> <li>□ Trauma of the spine</li> <li>□ Vascular disorder</li> </ul>	Vibration will neither make the passenger uncomfortable nor damage the structure	Inherently safe machinery design protects the vibration from discomforting passengers and from damaging the structure. Dynamic load test performed and found satisfactory	AS/NZS 1418.10:2011				ОК		

a	Risk Assessment according to AS 4024.1301		-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01					
	Identifie									on, AS 4024 or ISO I or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement
4.7	Radiation Hazards	<ul> <li>☐Lionising radiation source</li> <li>☐Low frequency electromagnetic radiation</li> <li>☐Optical radiation linfrared, visible and ultraviolet), including laser</li> <li>☐Radio frequency electromagnetic radiation</li> </ul>	Genetic mutation	Not relevant	Not relevant	N/A					N/A

Risk A according	Assessmen to AS 4024	-	machine: Mobile Elevated Work Platform date serial number: M0810JE			author: Lingong date: 2023.04.01			
Identifi	cation of hazards			Risk evaluation		tion, AS 4024 or ISO 1 or type I/II/III			
Phase Hazard group, of life type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F	P pl	Statement	
4.8 Material/ substance hazards	<ul> <li>Aerosol</li> <li>Biological and microbiological (viral or bacterial) agent</li> <li>Combustible</li> <li>Dust</li> <li>Explosive</li> <li>Fibre</li> <li>Flammable</li> <li>Fluid</li> <li>Fume</li> <li>Gas</li> <li>Mist</li> <li>Oxidizer</li> </ul>	□Breathing         difficulties,         suffocation         □Cancer         □Corrosion         □Effects on         reproductive         capability         ☑Fire         □Infection         □Mutation         □Poisoning         □Sensitization         □Static         electricity risk	Not relevant	Not relevant	N/A			N/A	

	Assessmen g to AS 4024				author: Lingong date: 2023.04.01				
lde	ntification of hazards			Risk evaluation		Risk			on, AS 4024 or ISO or type I/II/III
Phase Hazard gro of life type	up, Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F	Р	pl	Statement
4.9 Ergonomic hazards	<ul> <li>☑ Access</li> <li>☑ Disign or location of indicators and visual displays units</li> <li>☑ Design, location or identification of control devices</li> <li>☑ Effort</li> <li>☑ Effort</li> <li>☑ Flicker, dazzling, shadow, stroboscopic effect</li> <li>☑ Local lighting</li> <li>☑ Mental overload/underloa d</li> <li>☑ Posture</li> <li>☑ Repetitive activity</li> <li>☑ Visibility</li> </ul>	<ul> <li>☑ Discomfort</li> <li>☑ Fatigue</li> <li>☑ Musculoskelet al disorder</li> <li>☑ Stress</li> <li>☑ Any other (e.g.mechanica I, electrical) as a consequence of human error</li> </ul>	The position of control device need to be taken into account The access means need to be taken into account	Inherently safe machinery design	AS/NZS 1418.10:2011 as reference,				OK

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01					
	Identific	ation of hazards			Risk evaluation		R				ion, AS 4024 or ISO I or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement
4.10	Hazards associated with environment in which the machine is used	<ul> <li>☑ Dust and fog</li> <li>☑ Electromagnetic disturbance</li> <li>☑ Lighting</li> <li>☑ Moisture</li> <li>☑ Pollution</li> <li>☑ Snow</li> <li>☑ Temperature</li> <li>☑ Water</li> <li>☑ Wind</li> <li>□ Lack of oxygen</li> </ul>	<ul> <li>□ Burn</li> <li>□ Slight disease</li> <li>□ Slipping, falling</li> <li>□ Suffocation</li> <li>□ Any other as a consequence of the effect caused by the sources of the hazards on the machine or parts of the machine</li> </ul>	Working condition and EMC need to be considered	Inherently safe machinery design and construction and inform users of the residual risks: 1.2204/108/EEC addressed 2. Lighting for the control panel is provided and the lighting for access is indicated in the manual 3. Snow, wind loads are considered in the design and structural calculation 4. Ambient temperature is defined in the manual 5. All electric parts are protected by the enclosure with enough IP degree according to AS/NZS 1418.10:2011	AS/NZS 1418.10:2011 + MSD as reference,					ОК
4.11	Combination of hazards	E.g.repetitive activity + effort + high environmental temperature	E.g. dehydration, loss of awareness, heat stroke	Not relevant	Not relevant	N/A					N/A

a		Assessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: M0810JE		author: Lingong date: 2023.04.01				
	Identifi	cation of hazards			Risk evaluation		Risk			on, AS 4024 or ISO or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	SI	P	pl	Statement
4.12	Energy loss ,breaking down hazards	<ul> <li>➢ Failure of energy supply (incl. control circuits)</li> <li>➢ Unexpected ejection of machine parts or fluid</li> <li>□ Errors of fitting</li> </ul>	□ Being         thrown         □ Cutting or         severing         □ Drawing-in         or trapping         □         Entanglement         □ Friction or         abrasion         □ Injection         □ Shearing         □ Stabbing or         □ Suffocation	All risk related to unexpected starting or energy loss need to be taken into account	Inherently safe machinery design and construction, take necessary protection measures: 1. Brakes and cut-off valves are designed to be engaged as soon as the power losses, preventing the lift from falling.	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) + MSD as reference,				OK

risk assessment-M0810JE date: 01/06/2024 page 19 of 27

a	_	ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01		
	Identification of hazards						ion, AS 4024 or ISO 1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

ac	Risk Assessment according to AS 4024.1301		-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE	author: Lingong date: 2023.04.01						
	Identifica	ation of hazards			Risk evaluation		Ris				on, AS 4024 or ISO I or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Р	pl	Statement
5 Cle	aning										

a	-	ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE	author: Lingong date: 2023.04.01				
	Identifie	cation of hazards			Risk evaluation				on, AS 4024 or ISO or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P	pl	Statement
5.1	Hazards associated with all tasks	<ul> <li>Adjustments</li> <li>Cleaning, disinfection</li> <li>Dismantling /removal of parts, components, devices of the machine</li> <li>Housekeeping</li> <li>Isolation end energy dissipation</li> <li>Lubrication</li> <li>Replacement of worn parts</li> <li>Resetting</li> <li>Resetting fluid levels</li> <li>Verification of parts, components, devices of the machine</li> </ul>	<ul> <li>☑ Crushing</li> <li>☑ Cutting or severing</li> <li>☑ Friction or abrasion</li> <li>☑ Impact</li> <li>☑ Injection</li> <li>☑ Shearing</li> <li>☑ Stabbing or puncture</li> </ul>	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks: Refer to AS/NZS 1418.10:2011 and manual	AS/NZS 1418.10:2011 + MSD as reference,			OK

risk assessment-M0810JE date: 01/06/2024 page 22 of 27

ac	_	ssessmer to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01		
	Identific	ation of hazards			Risk evaluation	·		n, AS 4024 or ISO or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

acc	Risk Assessment			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE	author: Lingong date: 2023.04.01					
						Risk			tion, AS 4024 or ISO 1 or type I/II/III	
Phase H of life	lazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	SF	Р	pl	Statement
ass	azards sociated with tasks	⊠Adjustments         ⊠Dismantling         /removal of parts,         components,         devices of the         machine         ⊠Faultfinding         ⊠Isolation end         energy dissipation         ⊠Recovering         from control and         protective devices         failure         □Recovering         from jam         ⊠Repairing         ⊠Replacement of         parts,         components,         devices of the         machine         ⊠Rescue of         trapped persons         ⊠Resetting	<ul> <li>☑ Crushing</li> <li>☑ Cutting or severing</li> <li>□ Friction or abrasion</li> <li>☑ Impact</li> <li>□ Injection</li> <li>☑ Shearing</li> <li>☑ Stabbing or puncture</li> </ul>	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks: Refer to AS/NZS 1418.10:2011 clause 5 and manual	AS/NZS 1418.10:2011+ AS 60204.1-2005(+A1) + MSD as reference				OK

risk assessment-M0810JE date: 01/06/2024 page 24 of 27

Risk Assessment according to AS 4024.1301			-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE	author: Lingong date: 2023.04.01						
	Identification of hazards									on, AS 4024 or ISO I or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Р	pl	Statement
		Verification of parts, components, devices of the machine									

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE		author: Lingong date: 2023.04.01		
	Identific	ation of hazards			Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

1 Hazards associated with all tasks	associated with	Adjustments	Crushing	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks:	AS/NZS 1418.10:2011 as reference	ок
		<ul> <li>☑ Dismantling /removal of parts, components, devices of the machine</li> <li>☑ Housekeeping</li> <li>☑ Isolation end energy dissipation</li> <li>☑ Lubrication</li> </ul>	<ul> <li>□ Friction or abrasion</li> <li>□ Impact</li> <li>□ Injection</li> <li>□ Shearing</li> <li>□ Stabbing or puncture</li> </ul>		Refer to AS/NZS 1418.10:2011 clause 7		
		<ul> <li>☑ Replacement of worn parts</li> <li>☑ Resetting</li> </ul>					
		☐Restoring fluid levels					
		⊠ Verification of parts, components, devices of the machine					

8 Placing out of operation, disassembling, waste disposal

risk assessment-M0810JE date: 01/06/2024 page 26 of 27

Risk Assessment according to AS 4024.1301			-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: M0810JE	author: Lingong date: 2023.04.01							
Identification of hazards										ation, AS 4024 or ISO 9-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement	
8.1	Hazards associated with all tasks	<ul> <li>☑ Disconnection and energy dissipation</li> <li>☑ Dismantling</li> <li>☑ Lifting</li> <li>☑ Loading</li> <li>☑ Packing</li> <li>☑ Transportation</li> <li>☑ Unloading</li> </ul>	<ul> <li>□ Crushing</li> <li>□ Crushing or severing</li> <li>□ Friction or abrasion</li> <li>○ Impact</li> <li>□ Injection</li> <li>○ Shearing</li> <li>○ Stabbing or puncture</li> </ul>	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks: Refer to AS/NZS 1418.10:2011	AS/NZS 1418.10:2011 as reference					ОК	