Risk Assessment	Manufacturer: Lingong Heavy Machinery Co., Ltd. machine: Mobile Elevated Work Platform	author: Lingong date: 2023.1.1	
according to AS 4024.1301	serial number: T28J-H, T22J-H, T26J-H, T20J-H		LGMG

1	Determination of limits, intended use	See below		Reference to additional documents			
1.1	use allowed	The mobile elevated work platform	le elevated work platform allows users to work at a certain height				
1.2	restrictions, limits of use allowed	The machine cannot be used to ot	her propose	Manual			
1.3	foreseeable misuse/misapplication	See AS/NZS 1418.10:2011 clause 1					
2	Field of use	See below					
	private	N/A		N/A			
	commercial	Professional		Manual			
3	User population	Task	Qualification				
	qualified personnel	Required YES 1					
	laities	N/A	N/A	N/A			
	apprentices	N/A	N/A	N/A			
	private use only:	·	•				
	children (declare age class)	age above years		N/A			
	older people			N/A			
	handicapped	kind of handicap		N/A			
4	Materials	See below					
4.1	dangerous operating supplies	🛛 Electricity 🖾 Hydraulic 🔲 Pner	umatic Thermal Radiation	Manual			
4.2	Dangerous materials in the parts the machine is consisting of	The machine is not consisting of d	nachine is not consisting of dangerous materials				
4.3	Dangerous materials which may be processed by the machine	No dangerous materials processed	angerous materials processed by the machine				

The phases of life according to AS 4024 include: transport, assembling, installation, placing into operation, setup, teaching, programming, changeover, working process, cleaning, process interferences, troubleshooting, fault clearance, maintenance, placing out of operation, disassembling, waste disposal

Copyright: TÜV SÜD Product Service GmbH Gottlieb-Daimler-Straße 7 70794 Filderstadt phone: +49 (0)711 7005-295; Fax: -587 risk ass ssment-T20&an & damp;20@amp;21@amp;21 dat : 1/1/2024 rage 1 of 23

a	_	ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T		author: Lingong date: 2023.1.1		
	Identific	ation of hazards			Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

1.1	Fransport, assembl Hazards	Errors of fitting	Crushing	Machine, components and accessories	Inhoronthy opto maphingry desire	AS/NZS		OK
1.1	associated with				Inherently safe machinery design	1418.10:2011 and		on
	all tasks	⊠Lifting	Cutting or		and inform users of the residual	MSD as reference,		
			severing		risks:			
		Loading			Detail description for them an exterior			
			Friction or		Detail description for transportation, assembling and installation of machine			
		Packing	abrasion		are mentioned in manual.			
		⊠Transportation	⊠Impact					
			-					
		⊠Unloading						
		⊠Unpacking	Shearing					
			Shearing					
		Packing	Stabbing or					
		_	puncture					
		⊠Adjustments						
		Assembly						
		Connecting to						
		disposal system						
		(e.g. exhaust						
		system, waste water installation)						
		water installation)						
		Connection to						
		power supply						
		Demonstration						
		Feeding, filling,						
		loading of ancillary						
		fluids (e.g.						

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 2 of 23

a	-	ssessmen to AS 4024	it	machine: Mobile Elevated Work Platform	/anufacturer: Lingong Heavy Machinery Co., Ltd. nachine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T20J-H			
	Identification of hazards				·		ion, AS 4024 or ISO 1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement
		lubricant, grease, glue)						

a	-	ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: T28J-H, T22J-H, T26J-H,	author: Lingong date: 2023.1.1					SMG	
	Identific	ation of hazards				Ris			tion, AS 4024 or ISO -1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	FF	pl	Sta	atement
1.2	Hazards associated with all tasks	 Fixing, anchoring Preparations for the installation (e.g. foundations, vibration isolators) Running the machine without load Testing Trials with load or maximum load Fencing 	See above	See above	See above	AS/NZS 1418.10:2011 and MSD as reference,				ОК	
2 Pla	acing into operati	on	.1			1				1	
2.1	Hazards associated with all tasks	Refer to 1+3	Refer to 1+3	Refer to 1+3	Refer to 1+3	Refer to 1+3				ок	
	1	ogramming, chang									
3.1	Hazards associated with all tasks	Adjustment and setting of protective devices and other components	Crushing Cutting or severing	Machine and components	Inherently safe machinery design and inform users of the residual risks:	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) + MSD as reference,				ок	
Copyright:	TÜV SÜD Product Ser	•	1	•		1					

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 4 of 23

Risk Assessmen according to AS 4024	-			author: Lingong date: 2023.1.1					
Identification of hazards		Risk evaluation						ion, AS 4024 or ISO 1 or type I/II/III	
PhaseHazard group, typeOrigin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F	Р	pl	Statement	
Image: Section of the section of functional parameters of the machine Image: Section of function of function of the final product Image: Section of function of the final product	 ☐Friction or abrasion ☑ Impact ☐ Injection ☑ Shearing ☑ Stabbing or puncture 		Refer to AS/NZS 1418.10:2011, clause 7 and manual						

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 5 of 23

a	Risk As	ssessmen o AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T		author: Lingong date: 2023.1.1			
	Identification of hazards				Risk evaluation				ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P	pl	Statement

1	Mechanical	Acceleration,	Being run	Inherently safe machinery design		ok
	Hazards	deceleration (kinetic energy)	over □Being thrown	and construction, take necessary protection measures and inform users of the residual risks:	1418.10:2011 + AS 60204.1-2005(+A1)	
		Approach of a moving element to	⊠Crushing	Refer to AS/NZS 1418.10:2011, clause and manual	7	
		a fixed part	⊠Cutting or severing			
		Elastic elements	⊠Drawing-in or trapping			
		⊠Falling objects	⊠ Entanglement			
		Gravity (stored energy)	⊠Friction or abrasion			
		Height from the ground	⊠Impact			
		⊠High pressure				
		⊠Machinery mobility	⊠Shearing ⊠Slipping,			
		⊠Rotating elements	tripping and falling			
	Rough, slippery	Stabbing or puncture				
	surface					

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 6 of 23

a		ssessmen to AS 4024	-			author: Lingong date: 2023.1.1				
	Identification of hazards				Risk			Risk estimation, AS 4024 c 13849-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S I	FF	p pl	Statement
		⊠Stability ⊡Vacuum								

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T	author: Lingong date: 2023.1.1					
Phase	Phase Hazard group, Origin group, Potential			Risk evaluation occurrence or protection goal Description of solution		Standards		c estimation, AS 4024 13849-1 or type I/II/II		or type I/II/III
of life	type	type	consequences	occurrence or protection goal	Description of solution	Standarus	S F	Ρ	pl	Statement
4.2	See 4.1/4.3	See 4.1/4.3	See 4.1/4.3	See 4.1/4/3	See 4.1/4.3	See 4.1/4/3				See 4.1/4.3
4.3	Electrical Hazards	 □ Arc □ Electromagnetic phenomena □ Electrostatic phenomena □ Live parts □ Not enough distance to live parts under high voltage □ Overload □ Parts which have become live under fault conditions □ Short-circuit □ Thermal radiation 	⊠ Burn □ Chemical effects □ Effects on medical implants ⊠ Electrocution ⊠ Falling, being thrown ⊠ Fire □ Projection of molten particles ⊠ Shock	Any risk related to electrical fault will be checked automatically and view check according to manual	Inherently safe machinery design and construction: Refer to AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) No electronic circuit for safety circuit	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) as reference,				See 4.1
4.4	Thermal Hazards	Explosion Flame Objects or materials with a high or low temperature	Bun Dehydration Discomfort Frostbite	Not relevant	Not relevant					

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 8 of 23

ac	Risk Assessment according to AS 4024.1301					author: Lingong date: 2023.1.1					
	Identification of hazards				Risk					ion, AS 4024 or ISO 1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement
		☐Radiation from heat sources	☐Injuries by the radiation of heat sources ☐Scald								

а		Assessmen to AS 4024	machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T20J-H			author: Lingong date: 2023.1.1				
	· · · · · · · · · · · · · · · · · · ·				Risk evaluation		Risk			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	SF	P	pl	Statement
4.5	Noise hazards	 □Cavitation phenomena □Exhausting system □Gas leaking at high speed ○Manufacturing process (stamping, cutting etc) ○Moving parts □Scraping surfaces □Unbalanced rotating parts □Whisting pneumatics ○Worn parts 	 ☑ Discomfort ☑ Loss of awareness ☑ Loss of balance ☑ Permanent hearing loss ☑ Stress ☑ Tinnitus ☑ Tinedness ☑ Any other (e.g. mechanical, electrical) as a consequence of an interference with speech communicatio n or with acoustic signals 	Refer to comments.	Inform users of the residual risks: The manual has indicated the sound pressure level below 70dB	AS/NZS 1418.10:2011+MSD				ОК
4.6	Vibration Hazards	□Cavitation phenomena ⊠Misalignment of moving parts	⊠Discomfort □Low-back morbidity	Vibration will neither make the passenger uncomfortable nor damage the structure	Inherently safe machinery design protects the vibration from discomforting passengers and from damaging the structure. Dynamic load test performed and found	AS/NZS 1418.10:2011				ок

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 10 of 23

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T	author: Lingong date: 2023.1.1						
	Identification of hazards					Risk				on, AS 4024 or ISO I or type I/II/III	
Phase of life				occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement
		 Mobile equipment Scraping surfaces Unbalanced rotating parts Vibrating equipment Worn parts 	 ❑Neurological discorder ❑Osteo-articular discorder ❑Trauma of the spine ❑Vascular disorder 		satisfactory						

a		Assessmen to AS 4024		Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: T28J-H, T22J-H, T26J-H,	author: Lingong date: 2023.1.1) 3		
	Identification of hazards se Hazard group, Origin group, Potential				Risk evaluation				ation, AS 4024 or ISO)-1 or type I/II/III		
Phase of life	fe type type consequent			occurrence or protection goal	Description of solution	Standards	S F	ΡI	I Statement		
4.7	Radiation Hazards	 ☐Lionising radiation source ☐Low frequency electromagnetic radiation ☐Optical radiation linfrared, visible and ultraviolet), including laser ☐Radio frequency electromagnetic radiation 	 □ Burn □ Damage to eyes and skin □ Effects on reproductive capability □ Genetic mutation □ Headache, insomnia, etc. 	Not relevant	Not relevant	N/A			N/A		
4.8	Material/ substance hazards	 Aerosol Biological and microbiological (viral or bacterial) agent Combustible Dust Explosive Fibre Flammable ⊠Fluid 	□Breathing difficulties, suffocation □Cancer □Corrosion □Effects on reproductive capability ☑Fire □Infection □Mutation □Poisoning	Not relevant	Not relevant	N/A			N/A		

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 12 of 23

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T2	author: Lingong date: 2023.1.1	Ri		LGMG ation, AS 4024 or ISO	
Phase of life	ase Hazard group, Origin group, Potential			occurrence or protection goal	Description of solution	Standards	s	1384 P	9-1 or type I/II/III ol Statement
		☐Fume ☐Gas ☐Mist ☐Oxidizer	□ Sensitization □Static electricity risk						

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T	author: Lingong date: 2023.1.1				
	Identific	cation of hazards			Risk evaluation				tion, AS 4024 or ISO -1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	SF	P pl	Statement
4.9	Ergonomic hazards	 Access Disign or location of indicators and visual displays units Design, location or identification of control devices Effort Flicker, dazzling, shadow, stroboscopic effect Local lighting Mental overload/underloa d Posture Repetitive activity Visibility 	Discomfort	The position of control device need to be taken into account The access means need to be taken into account	Inherently safe machinery design	AS/NZS 1418.10:2011 as reference,			OK
4.10	Hazards associated with environment in	☑ Dust and fog☑ Electromagnetic	☐Burn ☐Slight	Working condition and EMC need to be considered	Inherently safe machinery design and construction and inform users of the residual risks:	AS/NZS 1418.10:2011 + MSD as reference,			ок

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 14 of 23

а	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: T28J-H, T22J-H, T26J-H,	n	author: Lingong date: 2023.1.1						
	Identification of hazards				Risk evaluation					ation, AS 4024 or ISO 9-1 or type I/II/III		
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S	FI	P pl	Statement		
	which the machine is used	disturbance Lighting Moisture Pollution Snow Temperature Water Wind Lack of oxygen	disease Slipping, falling Suffocation Any other as a consequence of the effect caused by the sources of the hazards on the machine or parts of the machine		 1.2204/108/EEC addressed 2. Lighting for the control panel is provided and the lighting for access is indicated in the manual 3. Snow, wind loads are considered in the design and structural calculation 4. Ambient temperature is defined in the manual 5. All electric parts are protected by the enclosure with enough IP degree according to AS/NZS 1418.10:2011 							

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machiner machine: Mobile Elevated Work Platforn serial number: T28J-H, T22J-H, T26J-H,	n	author: Lingong date: 2023.1.1					
	Identification of hazards				Risk evaluation		Ri				ion, AS 4024 or ISO I or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement
4.11	Combination of hazards	E.g.repetitive activity + effort + high environmental temperature	E.g. dehydration, loss of awareness, heat stroke	Not relevant	Not relevant	N/A					N/A
4.12	Energy loss ,breaking down hazards	 ☑ Failure of energy supply (incl. control circuits) ☑ Unexpected ejection of machine parts or fluid □ Errors of fitting 	□ Being thrown ⊠Cutting or severing □ Drawing-in or trapping □ Entanglement □ Friction or abrasion □ Injection □ Shearing □ Slipping, tripping and falling □ Suffocation	All risk related to unexpected starting or energy loss need to be taken into account	Inherently safe machinery design and construction, take necessary protection measures: 1. Brakes and cut-off valves are designed to be engaged as soon as the power losses, preventing the lift from falling.	AS/NZS 1418.10:2011 + AS 60204.1-2005(+A1) + MSD as reference,					ок

a	Risk Assessment according to AS 4024.1301			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T	Elevated Work Platform dat						
	Identifica	ation of hazards			Risk evaluation		Ris				AS 4024 or ISO type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	P	ol	Statement

a		ssessmen to AS 4024	-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T	Work Platform			
	Identific	ation of hazards			Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards S F P F		Statement

Hazards associated with all tasks	Adjustments	⊠Crushing ⊠Cutting or	Machine , components and accessories	Inherently safe machinery design and inform users of the residual	AS/NZS 1418.10:2011 + MSD as reference,		ОК
all tasks	disinfection	severing		risks:			
	Dismantling /removal of parts,	Friction or abrasion		Refer to AS/NZS 1418.10:2011 and manual			
	components, devices of the machine	⊠Impact					
	Housekeeping						
		Shearing					
	⊠Isolation end energy dissipation	Stabbing or puncture					
	⊠Replacement of worn parts						
	Resetting						
	□Restoring fluid levels						
	☐ Verification of parts, components, devices of the machine						

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 18 of 23

ad	Risk Assessment according to AS 4024.1301				author: Lingong date: 2023.1.1						
	Identific	ation of hazards		Risk evaluation			Ris				on, AS 4024 or ISO I or type I/II/III
Phase of life			occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement	

a	Risk Assessment according to AS 4024.1301		Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T		author: Lingong date: 2023.1.1			
	Identific	ation of hazards			Risk evaluation			ion, AS 4024 or ISO 1 or type I/II/III
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

6 Process interferences, troubleshooting, fault clearance											
6 Pi 6.1	Process interference Hazards associated with all tasks	☑ Adjustments ☑ Dismantling /removal of parts, components, devices of the machine ☑ Faultfinding ☑ Faultfinding ☑ Isolation end energy dissipation ☑ Recovering from control and protective devices failure □ Recovering from jam ☑ Replacement of parts, components, devices of the machine ☑ Rescue of	g, fault clearanc ⊠Crushing ©Crushing or severing □Friction or abrasion ©Impact □Injection ©Shearing ©Stabbing or puncture	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks: Refer to AS/NZS 1418.10:2011 clause 5 and manual	AS/NZS 1418.10:2011+ AS 60204.1-2005(+A1) + MSD as reference		ОК			
		trapped persons ⊠Resetting									

risk assessment-T20&22&26&28J-H.docx date: 1/1/2024 page 20 of 23

Risk Assessment according to AS 4024.1301			-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T	author: Lingong date: 2023.1.1						
	Identific	ation of hazards				Risk estimation, AS 4024 or ISC 13849-1 or type I/II/III					
Phase of life	Hazard group, type	Origin group, type	Potential consequences	s occurrence or protection goal Description of solution Standards					Ρ	pl	Statement
		⊠Verification of parts, components, devices of the machine									

a	Risk Assessment			Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T	author: Lingong date: 2023.1.1			
	Identific	ation of hazards					ion, AS 4024 or ISO 1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	S F P pl	Statement

.1	Hazards associated with all tasks	Adjustments	Crushing Cutting or severing	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks:	AS/NZS 1418.10:2011 as reference	ок
		⊠Dismantling /removal of parts,	☐Friction or , abrasion		Refer to AS/NZS 1418.10:2011 clause 7		
		components, devices of the machine					
		□Housekeeping	☐Injection ⊠Shearing				
		⊠Isolation end energy dissipation	Stabbing or puncture				
		Lubrication					
		Replacement of worn parts					
		Resetting					
		□Restoring fluid levels					
		⊠Verification of parts, components, devices of the machine					

Placing out of operation, disassembling, waste disposal 8

Risk Assessment according to AS 4024.1301			-	Manufacturer: Lingong Heavy Machinery machine: Mobile Elevated Work Platform serial number: T28J-H, T22J-H, T26J-H, T	author: Lingong date: 2023.1.1						
	Identific	ation of hazards								tion, AS 4024 or ISO -1 or type I/II/III	
Phase of life	Hazard group, type	Origin group, type	Potential consequences	occurrence or protection goal	Description of solution	Standards	s	F	Ρ	pl	Statement
8.1	Hazards associated with all tasks	 ☑ Disconnection and energy dissipation ☑ Dismantling ☑ Lifting ☑ Loading ☑ Packing ☑ Transportation ☑ Unloading 	 □Crushing □Crushing or severing □Friction or abrasion ☑Impact □Injection ☑Shearing ☑Stabbing or puncture 	Machine , components and accessories	Inherently safe machinery design and inform users of the residual risks: Refer to AS/NZS 1418.10:2011	AS/NZS 1418.10:2011 as reference					ОК